

THE PERFECT LOCK

BLOCKTILE

LOOSE LAYING
SELF-BLOCKING
VINYL FLOOR TILES

SOGEA

THE NATURE OF PLASTICS

 MADE IN ITALY

BLOCKTILE



0811



0816



0504



0714



0708



0406




0401



0400



0404



Art 2081 and 2080

Tiles (see diagram):
(50 x 50cm)

Weight: 6kg/ square
meter

Thickness: 4 mm

Box of 20 tiles equals
4.7 square meters



0813

Can be applied easily on any surface, without professional help.
No adhesive needed (we suggest to use some glue in the proximity
of entrance areas). No special maintenance needed.



10



34



61



90



52



56



80



23



20



As for all vinyl flooring, prolonged contact with tires or other rubber
objects can cause indelible brown marks. Further, as adhesive is not
used to fix tiles, forklifts and carts are not recommended. Beyond 50
sq. meters the use of expansion joints is mandatory. Installation should
be carried at least at 18°C. This temperature should be maintained for
24 hours before and after installation.

BLOCKTILE Granulate (A.2081)

Granulate Blocktile
is a resilient flooring in
self blocking tiles made
with rigid PVC granules,
elastomers, and inert
mineral loads.

Fire resistance:

CE class Bfl-s1

Indentation:

EN 433 0.04 mm

Light fastness:

EN ISO 105-B02 7

Wear resistance:

EN 660-2 2.0/1.5 mm³

Shore hardness A:

94 (DIN 53505)

**Resistance to chemical
agents:** good with oils and
grease, detergents and
the majority of alkali and
diluted acids.

BLOCKTILE Solid (A.2080)

Solid Blocktile is a
resilient flooring made
with recyclable vinyl
resins, elastomers, and
inert mineral charges.

Particularly suited to
flooring in areas where
children are present,
such as kindergartens,
playrooms, small gyms.

Fire resistance:

CE class Bfl-s1

Shore hardness A:

75-80 (DIN 53505)

Light fastness:

6-7 blue scale

Resistant to chemical

agents: Good with
the majority of diluted
chemical agents.